

Scalectoat Model Paint - Thinners & Miscellaneous

Paint Touch-Up Pen \$4.79

1 Ounce Bottles \$3.49

2 Ounce Bottles \$5.29

6 Ounce Spray Cans \$7.99

Scalectoat I (for use on Brass, Metal, & Wood)

Name	1 Ounce		2 Ounce		6 Ounce	
	Item #	Qty.	Item #	Qty.	Item #	Qty.
Thinners - Scalectoat I						
8 oz. Thinner \$6.19	10487		N/A	N/A	N/A	N/A
1 quart Thinner \$13.29	10499		N/A	N/A	N/A	N/A
2 oz. Thinner \$3.59	N/A	N/A	10502		N/A	N/A
Flat Glaze	10511		10512		N/A	N/A
Gloss Glaze	10521		10522		10526	
Satin Finish	N/A	N/A	N/A	N/A	10566	
Sanding Sealer	10531		10532		10536	
16 oz. Paint Remover \$11.69	10568		N/A	N/A	N/A	N/A
Sanding Sealer Thinner \$3.59	N/A	N/A	10572		N/A	N/A
Metal Stripper 1 quart \$13.49	10599		N/A	N/A	N/A	N/A

Scalectoat II (for use on Plastic)

Name	1 Ounce		2 Ounce		6 Ounce	
	Item #	Qty.	Item #	Qty.	Item #	Qty.
Thinners - Scalectoat II						
8 oz. Thinner \$6.19	20487		N/A		N/A	
1 quart Thinner \$13.29	20499		N/A		N/A	
2 oz. Thinner \$3.59	N/A		20502		N/A	
Miscellaneous						
Counter Display Rack \$65.00 (accommodates 180 bottles)					S999	
Counter Display Rack \$65.00 (accommodates 100 spray cans)					S111	
Color Chip Chart \$2.00					S222	

RECOMMENDED STEPS FOR APPLICATION

Scalectoat Paint requires no primer, and if properly applied, one thin coat will cover and adhere so tightly it is almost impossible to get off.

- Disassemble model completely, be certain to remove all parts that will not accept at least 175 degree temperature.
- Thoroughly clean all parts to be sprayed, using any type of household cleanser or cleaner. Clean and rinse with extremely hot water. Oven dry or air dry all parts.
- If brushing, no thinning is required. If spraying, the recommended air pressure is 18 to 25 psi.
- Using Scalectoat thinner, thin paint to at least a 2 to 1 ratio (amount of thinner can vary with color. Some thicker pigments, reds & oranges in particular, may require slightly more or less thinner. 2 parts paint to 1 part thinner is a good general starting point). Test spray on the inside of the model before application.
- Apply the paint with even strokes at a distance of about 6 inches away from the model.
- Preheat your oven to 175 . The model should be "baked" for approximately 2 hours. Better adhesion of the paint will result if the model is oven or heat dried. (A hand held hair dryer will work fine).
- If more than one color is to be applied, oven dry at least 60 minutes between colors.
- Because of the high gloss finish of Scalectoat it will accept decals without any other preparation.
- To protect the finish and hide any decal film, use Scalectoat Gloss or Flat Glaze, they are compatible and we recommend a 2/3 gloss to 1/3 flat mixture to achieve a nice satin finish. Whatever finish you choose, use Scalectoat thinner, and mix a ratio of at least 1 part over spray to 1 part thinner.
- Application of Scalectoat II is identical to Scalectoat I with the exception of the "baking" process.

Name _____
 Address _____
 City _____ State _____ Zip _____
 Phone _____
 E-mail: _____

Card Type



MONEY ORDER CASHIER'S CHECK

PERSONAL CHECKS NOT ACCEPTED

Card # _____ Exp. _____
 Last 3 digits below black strip on back of card _____
 Signature _____

Shipping Charges		Merchandise Total \$
Up to \$19.99	\$7.50	PA Res. 6% Sales Tax \$
\$20.00 to \$39.99	\$9.00	Sub Total \$
\$40.00 to \$59.99	\$10.50	Shipping (see chart) \$
\$60.00 to \$79.99	\$12.50	Grand Total \$
\$80.00 to \$99.99	\$14.00	
COD Fee	\$10.00	

(Add \$2.50 Shipping For Every \$20.00 Over \$100.00)
 Prices & Fees Subject To Change

Thank You For Your Order! All Sales Final!

Sorry - We Cannot Ship Paint and Paint Related Products (thinners, etc.) Outside Of The Continental United States nor can we Honor Paint Sales To Texas!

Weaver Models

P.O. Box 231 ~ Northumberland, PA 17857

Phone: 570-473-9434 Fax: 570-473-3293

E-mail: customerservice@weavermodels.com Web Site: www.weavermodels.com